



DIN 7753 Teil Part 1/ISO 4184/BS 3790

USA-Standard RMA/MPTA

Profil Profile SPB	Profil Profile SPC	Profil Profile 8V/25N	
Richtlänge Datum length ISO, DIN, BS L _d (mm)	Richtlänge Datum length ISO, DIN, BS L _d (mm)	Riemenbezeichnung Belt no. (Zoll inch)	(Außenlänge Outside length mm)
<p>BM BQ = 10 Stück pieces</p> <p>1500• 1600• 1700• 1800• 1900• 2000• 2120• 2240• 2360• 2500• 2650• 2800• 3000• 3150• 3350• 3550• 3750• 4000• 4250• 4500• 4750• 5000•</p> <p>BM BQ = 5 Stück pieces</p> <p>5300• 5600• 6000• 6300• 6700• 7100• 7500• 8000•</p>	<p>BM BQ = 10 Stück pieces</p> <p>2000• 2120• 2240• BM BQ = 5 Stück pieces</p> <p>2360• 2500• 2650• 2800• 3000• 3150• 3350• 3550• 3750• 4000• 4250• 4500• 4750• 5000• BM BQ = 3 Stück pieces</p> <p>5300• 5600• 6000• 6300• 6700• 7100• 7500• 8000• 8500• 9000•</p>	<p>BM BQ = 1 Stück piece</p> <p>8V 1600• 8V 1700• 8V 1800• 8V 1900• 8V 2000• 8V 2120• 8V 2240• 8V 2360• 8V 2500• 8V 2650• 8V 2800• 8V 3000• 8V 3150• 8V 3350• 8V 3550•</p>	<p>25N 4064 25N 4318 25N 4572 25N 4826 25N 5080 25N 5385 25N 5690 25N 5994 25N 6350 25N 6731 25N 7112 25N 7620 25N 8001 25N 8509 25N 9017</p>

Anfertigungsware. Non stock items.

Weitere Abmessungen und Profile auf Anfrage. Further sizes and profiles on request.

<p>Maximale Fertigungslänge Maximum manufacturing length: 8000 mm</p> <p>Mindest-Abnahmemenge Minimum production quantity: 1500 mm – 1800 mm = 25 Stück pieces über over 1800 mm = 23 Stück pieces</p> <p>Gewicht Belt weight: ≈ 0,206 kg/m</p>	<p>Maximale Fertigungslänge Maximum manufacturing length: 10000 mm</p> <p>Mindest-Abnahmemenge Minimum production quantity: ab from 2000 mm = 16 Stück pieces</p> <p>Gewicht Belt weight: ≈ 0,389 kg/m</p>	<p>Maximale Fertigungslänge Maximum manufacturing length: 12065 mm L_a</p> <p>Mindest-Abnahmemenge Minimum production quantity: ab from 4064 mm L_a = 14 Stück pieces</p> <p>Gewicht Belt weight: ≈ 0,603 kg/m</p>
---	--	--